



Optional Parts

Popular Options:

SPECIFIC RESET POINT RANGE – (Calibrated Switch)

PIGTAILS – Standard, Non-jacketed (“L” Interface)
12” long included in price, longer lengths available
18 AWG, 20 AWG Wire in various colors

PIGTAIL WITH PVC JACKET (“L” Interface)
12” length, longer lengths available

UL and/or CSA – Consult Factory
Some product is covered by UL/CSA approval under the following file numbers: UL E 109178 - CSA LR62173 - P88, P117, W117, P119.
UL E 123402 – CSA LR87500 – Wiring harness

PIN RECEPTACLE – AMP 60789-2 or equal
Three per set (“T” interface)

VOLTAGE SPIKE ARRESTOR – AC/DC Voltage,
SPST/SPDT Switches

BAR CODING
R/C CIRCUITS FOR CURRENT BELOW 10mA
O RINGS (J205, P605, J705 only)
Special materials upon request

ROLL STAMPING/STENCILING
COMPUTER DIAGNOSIS CAPABILITY

SHRINK TUBING

CONVOLUTED CONDUIT

LABELING

TEFLON TAPE – Available on NPT Fittings

THREAD LOCKER – Available on all Fittings

Fittings:

Most models can be obtained with a variety of fittings.
Some common fittings are shown below.
Please specify when ordering.



Adapters:

Models P100, P119 and J705 are available with optional port thread adapters.



Conduit Adapter pressure switch protector, equivalent to NEMA Type III when mounted as shown. 1/2" NPT Male Connection. Limited to "L", "TB" and "TS" Interfaces. Material, anodized aluminum.
301-300 for use with:
Models P117, P119
320-300 for use with:
Models J205, J705
323-605 for use with:
Model P605
Consult factory for NEMA IV models

