

TP

-

XXX

-

NX

-

TX

-

LX

-

WX

-

CX

XXX Temperature	NX Circuit	TX Thread	LX Probe Length	WX Wire Length	CX Connector
<u>Standard</u> <b>075-250</b> 75°F-250°F 25°F increments Accuracy +/-5°F	<u>Standard</u> <b>NO</b> Normally Open  <b>NC</b> Normally Closed	<u>Standard</u> ½" NPT  <u>Made To Order</u> <b>T1</b> – 3/8" NPT <b>T2</b> – ¼" NPT	<u>Standard</u> 5/8"  <u>Made To Order</u> <b>L1</b> – ½ " <b>L2</b> – ¾" For ½" NPT thread only <b>L3</b> – 3"	<u>Standard</u> 36"	<u>Standard</u> Lead Wires  <u>Made To Order</u> <b>C1</b> – Weather / Metri-Pack <b>C2</b> – Deutsch
<u>Custom</u> 50°F-250°F at any point		<u>Custom</u> <b>T0</b> – Custom Examples: ¾" NPT ½ " BSPP M18 SAE ½" BSPT M16 SAE	<u>Custom</u> <b>L0</b> – Custom Example: 0"	<u>Custom</u> <b>W0</b> - Custom	<u>Custom</u> <b>C0</b> – Custom <b>C3</b> – Terminal Blade <b>C4</b> – ½" NPT Male w/ Leads

Note: If part number doesn't contain TX, LX, WX, or CX, the standard will be selected for those parameters.