

# Optional Parts

**Popular Options:**

- **SPECIFIC RESET POINT RANGE** – (Calibrated Switch)
- **PIGTAILS** – Standard, Non-jacketed ("L" Interface) 12" long included in price, longer lengths available 18 AWG, 20 AWG Wire in various colors
- **PIGTAIL WITH PVC JACKET** ("L" Interface) 12" length, longer lengths available
- **UL and/or CSA – Consult Factory** Some product is covered by UL-CSA approval under the following file numbers: UL E 109178 – CSA LR62173 – P88, P117, W117, P119, J205. UL E 123402 – CSA LR87500 – Wiring harness
- **PIN RECEPTACLE** – AMP 60598-4 or equal Three per set ("T" interface)
- **VOLTAGE SPIKE ARRESTOR** – AC/DC Voltage, SPST/SPDT Switches
- **BAR CODING**
- **R/C CIRCUITS FOR CURRENT BELOW 10mA**
- **O-RINGS (J205, P605, J705 only)** Special materials upon request
- **ROLL STAMPING/STENCILING**
- **COMPUTER DIAGNOSIS CAPABILITY**
- **SHRINK TUBING**
- **CONVOLUTED CONDUIT**
- **LABELING**
- **TEFLON TAPE** – Available on NPT Fittings
- **THREADLOCKER** – Available on all Fittings

**Adapters:**

Models P100, P119 and J705 are available with optional port thread adapters.



**1/8" NPT to 1/4" NPT**



**1/8" NPT to 7/16-20 SAE**



**1/8" NPT to 9/16-18 SAE**

**Fittings:**

Most models can be obtained with a variety of fittings. Some common fittings are shown below. Please specify when ordering.



**1/8 NPT Fitting**

(Optional for P605)



**1/4 NPT Fitting**

(Optional for P117, F119 J205, W117)



**7/16-20 Thread Fitting**

(Optional for P117, J205)



**1/4" VCR Fitting**

(Optional for P117, W117, J205)



**1/2-20 SAE Fitting with Optional O-Ring**

(Optional zinc diecast for P93)

(Optional stainless steel for P95)



**KF16 Flange**

(Optional for W117, 1.18" Diam)